

UL2464-OHFR-PCPVV-SB

Example of printing E79011-H  AWG 2464 KOURIKI-SLIP LF(特殊種) TATSUTA

Model	Conductor			Insulation		Sheath		Weight kg/km	Conductor resistance (20°C) Ω /km	Insulation resistance (20°C) M Ω /km	Test Voltage V·1min	Allowable Current (30°C) A	Length m
	Size AWG	Const- ruction No./mm	OD mm	Thick- ness mm	OD mm	Thick- ness mm	OD mm						
21AWG × 1P	21 (0.5mm ²)	3/33/0.08	1.1	0.5	2.1	1.2	7.3	75	50.8 or under	5 or more	AC 2000	9.5	100 (B)
21AWG × 2P						11.5	165	8.0					
21AWG × 3P						12.0	175	6.7					
21AWG × 4P						13.0	205	6.1					
21AWG × 5P						14.0	220	5.6					
21AWG × 6P						15.0	255	5.3					
21AWG × 7P						16.0	290	5.1				50 (B)	
21AWG × 8P						17.5	325	4.9					
21AWG × 10P						19.0	405	4.5					
21AWG × 15P						21.0	515	3.9					
21AWG × 20P						1.6	24.0	675				3.5	100(D)
19AWG × 1P	19 (0.75mm ²)	3/50/0.08	1.4	0.5	2.4	1.2	7.8	85	33.5 or under	5 or more	AC 2000	12.1	100 (B)
19AWG × 2P						12.5	190	10.2					
19AWG × 3P						13.0	210	8.6					
19AWG × 4P						14.0	245	7.7					
19AWG × 5P						15.0	270	7.2					
19AWG × 6P						16.5	315	6.8				50 (B)	
19AWG × 7P						17.5	360	6.5					
19AWG × 8P						19.0	445	6.3					
19AWG × 10P						20.5	495	5.8					
17AWG × 1P	17 (1.25mm ²)	7/33/0.08	1.6	0.6	2.8	1.2	8.8	110	21.1 or under	5 or more	AC 2000	16.0	100 (B)
17AWG × 2P						14.0	235	13.4					
17AWG × 3P						14.5	265	11.3				50 (B)	
17AWG × 4P						15.5	315	10.2					

- Shield is included in the cable design.
- Unshielded type is also available. Model : UL2464-OHFR-PCPVV
- "B" in Length part means "Bundle", "D" in Length part means "Drum".