

UL2464-OHFR-PCTV(with shield :-SB)

\*Example of printing\* E79011-H  AWG 2464 KOURIKI-SLIP LF(材料印) TATSUTA

Instrumentation/FA Cables

Model	Conductor			Insulation		Sheath		Weight kg/km	Conductor resistance (20°C) Ω /km	Insulation resistance (20°C) MΩ /km	Test Voltage V 1min	Allowable Current (30°C) A	Length m
	Size	Const- ruction	OD	Thick- ness	OD	Thick- ness	OD						
	AWG	No./mm	mm	mm	mm	mm	mm						
21AWG × 2C	21 (0.5mm <sup>2</sup> )	3/33/0.08	1.1	0.3	1.7	1.0	5.6	41	50.8 or under	1000 or more	AC 2000	9.1	100 (B)
21AWG × 3C						6.4	60	7.8					
21AWG × 4C						6.9	70	7.0					
21AWG × 5C						7.3	80	6.4					
21AWG × 6C						7.9	90	6.1					
21AWG × 8C						9.0	120	5.6					
21AWG × 10C						10.0	145	5.2					
21AWG × 12C						10.0	150	4.8					
21AWG × 15C						11.5	185	4.4					
21AWG × 20C						13.0	235	4.0					
21AWG × 30C						14.5	325	3.5					
19AWG × 2C						19 (0.75mm <sup>2</sup> )	3/50/0.08	1.4				0.3	
19AWG × 3C	7.0	70	10.0										
19AWG × 4C	7.5	85	8.9										
19AWG × 5C	8.1	100	8.3										
19AWG × 6C	8.7	115	7.8										
19AWG × 8C	9.9	150	7.2										
19AWG × 10C	12.0	205	6.8										
19AWG × 12C	12.0	205	6.2										
19AWG × 15C	12.5	245	5.7										
19AWG × 20C	14.0	325	5.2										
19AWG × 30C	16.5	440	4.5										
17AWG × 2C	17 (1.25mm <sup>2</sup> )	7/33/0.08	1.6	0.3	2.2				1.2	6.9	70		21.1 or under
17AWG × 3C						7.4	85	13.0					
17AWG × 4C						8.0	105	11.6					
17AWG × 5C						8.6	120	10.7					
17AWG × 6C						9.1	145	10.1					
17AWG × 8C						11.0	205	9.3					
17AWG × 10C						12.5	260	8.8					
17AWG × 12C						12.5	260	8.0					
17AWG × 15C						13.5	310	7.4					
17AWG × 20C						15.5	430	6.8					
17AWG × 30C						18.0	570	5.9					

- The O.D. of shielded type will be 0.5mm bigger than that of unshielded type.
- "B" in Length part means "Bundle", "D" in Length part means "Drum".