

UL2464-OHFR-PCPTV-SB

Example of printing E79011-H  AWG 2464 KOURIKI-SLIP LF(キナイレウ) TATSUTA

Model	Conductor			Insulation		Sheath		Weight kg/km	Conductor resistance (20°C) Ω /km	Insulation resistance (20°C) M Ω /km	Test Voltage V·1min	Allowable Current (30°C) A	Length m
	Size	Const- ruction	OD	Thick- ness	OD	Thick- ness	OD						
	AWG	No./mm	mm	mm	mm	mm	mm						
21AWG × 1P	21 (0.5mm ²)	3/33/0.08	1.1	0.3	1.7	1.2	6.5	60	50.8 or under	1000 or more	AC 2000	9.4	100 (B)
21AWG × 2P							9.2	105				7.8	
21AWG × 3P							9.7	125				6.5	
21AWG × 4P						1.5	11.5	160				5.9	
21AWG × 5P							12.0	195				5.4	
21AWG × 6P							13.0	215				5.1	
21AWG × 7P							14.0	240				4.9	
21AWG × 8P							15.0	270				4.7	
21AWG × 10P							15.5	315				4.3	
21AWG × 15P						17.5	410	3.7				50 (B)	
21AWG × 20P						20.0	550	3.4				100(D)	
19AWG × 1P						19 (0.75mm ²)	3/50/0.08	1.4				0.3	
19AWG × 2P	10.5	130	10.0										
19AWG × 3P	11.5	170	8.4										
19AWG × 4P	12.5	200	7.6										
19AWG × 5P	1.5	13.5	240	7.0									
19AWG × 6P		14.5	270	6.6									
19AWG × 7P		15.5	305	6.3									
19AWG × 8P		16.5	345	6.1									
19AWG × 10P	17.5	400	5.6	50 (B)									
17AWG × 1P	17 (1.25mm ²)	7/33/0.08	1.6	0.3	2.2				1.2	7.4	80		21.1 or under
17AWG × 2P						11.5	170	13.1					
17AWG × 3P						1.5	12.0	200	11.0				
17AWG × 4P							13.0	240	9.8				

- Shield is included in the cable design.
- Unshielded type is also available. Model : UL2464-OHFR-PCPTV
- "B" in Length part means "Bundle", "D" in Length part means "Drum".