

UL2854-OHFR-PCPTV-SB

ケーブル表面表示(例) E79011-H  AWG 2854 KOURIKI-SLIP LF TATSUTA

型式	導体			絶縁体		シース		概算 質量 kg/km	導体 抵抗 Ω/km	絶縁 抵抗 MQ·km	耐電圧 V/1分間	許容 電流 (40℃) A	製品 条長 m									
	断面積	構成	外径	厚さ	外径	厚さ	仕上 外径															
	AWG	本/mm	mm	mm	mm	mm	mm															
25AWG × 1P	25 (0.2mm ²)	40/0.08	0.58	0.2	1.0	0.8	4.2	25	123 以下	1000 以上	AC500	5.0	100 (束)									
25AWG × 2P						6.2	49	4.2														
25AWG × 3P						6.5	60	3.5														
25AWG × 4P						6.9	70	3.1														
25AWG × 5P						7.4	80	2.9														
25AWG × 6P						7.9	90	2.7														
25AWG × 7P						8.8	110	2.6														
25AWG × 8P						9.3	120	2.5														
25AWG × 10P						9.7	130	2.3														
25AWG × 12P						10.5	150	2.2														
25AWG × 15P						11.0	175	2.0														
25AWG × 20P						12.5	215	1.8														
25AWG × 25P						15	270	1.6				50(束)										
23AWG × 1P						23 (0.3mm ²)	60/0.08	0.72				0.2		1.1	0.8	4.5	31	82.2 以下	1000 以上	AC500	6.4	100 (束)
23AWG × 2P															6.4	65	5.3					
23AWG × 3P	6.7	75	4.4																			
23AWG × 4P	7.3	80	4.0																			
23AWG × 5P	8.1	100	3.7																			
23AWG × 6P	8.7	115	3.5																			
23AWG × 7P	9.3	130	3.3																			
23AWG × 8P	9.9	160	3.2																			
23AWG × 10P	11.0	165	2.9																			
23AWG × 12P	11.0	170	2.7																			
23AWG × 15P	12.0	205	2.5																			
23AWG × 20P	14.0	280	2.3	50																		
23AWG × 25P	15.0	310	2.1	(束)																		
21AWG × 1P	21 (0.5mm ²)	3/33/0.08	1.1	0.3	1.7				1.2	6.5	60		50.8 以下		1000 以上	AC500	9.4				100 (束)	
21AWG × 2P									8.9	105	7.7											
21AWG × 3P						9.4	130	6.4														
21AWG × 4P						11.0	165	5.8														
21AWG × 5P						12.0	190	5.4														
21AWG × 6P						12.5	220	5.1														
21AWG × 7P						13.5	255	4.8														
21AWG × 8P						14.5	285	4.7														
21AWG × 10P						15.5	300	4.3	50													
21AWG × 12P						16.0	350	4.0	(束)													
21AWG × 15P						17.0	405	3.7														
21AWG × 20P						20.0	540	3.3	100(D)													

- ・線心配列は、線心配列表のパターン⑤ (P.24) 参照。
- ・シールドを含む設計となります。
- ・シールドの無いタイプも製造可能です。 型番：UL2854-OHFR-PCPTV
- ・製品条長は "D" はドラム巻き形状となります。

計装用ケーブル (F・A・計装)