

UL2854-OHFR-PCPVV-SB

\*ケーブル表面表示(例)\* E79011-H  AWG 2854 KOURIKI-SLIP LF TATSUTA

計装用ケーブル(FA・計装)

型式	導体			絶縁体		シース		概算 質量 kg/km	導体 抵抗 Ω /km	絶縁 抵抗 MΩ・km	耐電圧 V/1分間	許容 電流 (40℃) A	製品 条長 m										
	断面積	構成	外径	厚さ	外径	厚さ	仕上 外径																
	AWG	本 /mm	mm	mm	mm	mm	mm																
25AWG × 1P	25 (0.2mm <sup>2</sup> )	40/0.08	0.58	0.25	1.1	0.8	4.4	28	123 以下			5.0	100 (束)										
25AWG × 2P						6.6	60	4.2															
25AWG × 3P						6.9	65	3.6															
25AWG × 4P						7.3	75	3.2															
25AWG × 5P						7.8	85	2.9															
25AWG × 6P						8.8	105	2.8															
25AWG × 7P						9.4	120	2.7															
25AWG × 8P						9.9	130	2.6															
25AWG × 10P						10.5	135	2.3															
25AWG × 12P						11.0	140	2.2															
25AWG × 15P						12.0	175	2.0															
25AWG × 20P						13.5	220	1.8															
25AWG × 25P						14.5	260	1.7															
23AWG × 1P						23 (0.3mm <sup>2</sup> )	60/0.08	0.72						0.25	1.2	0.8	4.7	33	82.2 以下	5 以上	AC500	6.4	100 (束)
23AWG × 2P																7.1	70	5.4					
23AWG × 3P	7.4	80	4.5																				
23AWG × 4P	7.9	90	4.0																				
23AWG × 5P	8.9	115	3.8																				
23AWG × 6P	9.5	130	3.5																				
23AWG × 7P	10.5	145	3.4																				
23AWG × 8P	11.0	165	3.3																				
23AWG × 10P	11.5	165	3.0																				
23AWG × 12P	12.0	180	2.8																				
23AWG × 15P	13.5	240	2.6																				
23AWG × 20P	15.0	300	2.3																				
23AWG × 25P	16.0	330	2.2																				
21AWG × 1P	21 (0.5mm <sup>2</sup> )	3/33/0.08	1.1	0.4	1.9				1.2	6.9	65	50.8 以下					9.4	100 (束)					
21AWG × 2P									10.5	130	7.8												
21AWG × 3P						11.0	155	6.6															
21AWG × 4P						12.0	180	5.9															
21AWG × 5P						13.0	210	5.5															
21AWG × 6P						14.0	240	5.2															
21AWG × 7P						15.0	275	4.9															
21AWG × 8P						16.0	315	4.8															
21AWG × 10P						17.5	320	4.4															
21AWG × 12P						18.0	370	4.1															
21AWG × 15P						19.5	440	3.8															
21AWG × 20P						22.0	570	3.4															

- ・線心配列は、線心配列表のパターン③ (P.23) 参照。
- ・シールドを含む設計となります。
- ・シールドの無いタイプも製造可能です。 型番：UL2854-OHFR-PCPVV
- ・製品条長は "D" はドラム巻き形状となります。