

### UL2854-OHR-PCVV(Solid sheath type)

\*Example of printing\* E79011-H  AWG 2854 KOURIKI-SLIP LF TATSUTA

Model	Conductor			Insulation		Sheath		Weight kg/km	Conductor resistance (20°C) Ω /km	Insulation resistance (20°C) M Ω /km	Test Voltage V·1min	Allowable Current (30°C) A	Length m
	Size	Const- ruction	OD	Thick- -ness	OD	Thick- -ness	OD						
	AWG	No./mm	mm	mm	mm	mm	mm						
28AWG × 2C	28 (0.1mm <sup>2</sup> )	20/0.08	0.41	0.15	0.7	0.6	2.6	9	247 or under	5 or more	AC500	2.9	100 (B)
28AWG × 3C						0.55		10				2.4	
26AWG × 2C	26 (0.15mm <sup>2</sup> )	30/0.08	0.51	0.2	0.9	0.6	3.0	12	164 or under			3.8	100 (B)
26AWG × 3C						0.5		13				3.2	
25AWG × 2C	25 (0.2mm <sup>2</sup> )	40/0.08	0.58	0.25	1.1	0.6	3.4	13	123 or under			4.7	100 (B)
25AWG × 3C						0.55		16				3.9	
23AWG × 2C	23 (0.3mm <sup>2</sup> )	60/0.08	0.72	0.25	1.2	0.8	4.0	19	82.2 or under			6.1	100 (B)
23AWG × 3C						0.7		24				5.0	

· "B" in Length part means "Bundle", "D" in Length part means "Drum".

### UL2854-OHR-PCTV(Solid sheath type)

\*Example of printing\* E79011-H  AWG 2854 KOURIKI-SLIP LF TATSUTA

Model	Conductor			Insulation		Sheath		Weight kg/km	Conductor resistance (20°C) Ω /km	Insulation resistance (20°C) M Ω /km	Test Voltage V·1min	Allowable Current (30°C) A	Length m
	Size	Const- ruction	OD	Thick- -ness	OD	Thick- -ness	OD						
	AWG	No./mm	mm	mm	mm	mm	mm						
28AWG × 2C	28 (0.1mm <sup>2</sup> )	20/0.08	0.41	0.15	0.7	0.6	2.6	9	247 or under	1000 or more	AC500	2.9	100 (B)
28AWG × 3C						0.55		10				2.4	
26AWG × 2C	26 (0.15mm <sup>2</sup> )	30/0.08	0.51	0.2	0.9	0.6	3.0	13	164 or under			3.9	100 (B)
26AWG × 3C						0.5		14				3.2	
25AWG × 2C	25 (0.2mm <sup>2</sup> )	40/0.08	0.58	0.2	1.0	0.7	3.4	16	123 or under			4.7	100 (B)
25AWG × 3C						0.65		18				3.9	
23AWG × 2C	23 (0.3mm <sup>2</sup> )	60/0.08	0.72	0.2	1.1	0.9	4.0	23	82.2 or under			6.2	100 (B)
23AWG × 3C						0.8		25				5.1	

· "B" in Length part means "Bundle", "D" in Length part means "Drum".